



POWER			RELAY CONNECTIONS					
1	2	3	4	5	6	7	8	9
GND	L1	L2	NC	C	NO	NC	C	NO

DIMENSIONS		
A	CSL	C
1 1/4 (32)	2 (51)	2 1/2 (64)
2 (51)	3 1/2 (89)	5 1/2 (140)
8 (203)	10 (254)	12 (305)

NOTES:

- METAL WETTED PARTS ARE 316 STAINLESS STEEL.
- INSULATION MATERIAL IS POLYETHERETHERKETONE (PEEK).
- OPTIONAL DRILLED AND TAPPED FLANGE MOUNTING AVAILABLE. MINIMUM FLANGE SIZE: ASME 1" 150#; DIN DN25 PN16.
- THE SENSING ELEMENT IS DESIGNED TO FIT THROUGH A 3/4" HALF COUPLING. HOWEVER, THE 7/8" DIAMETER WILL NOT FIT INTO A 3/4" PIPE.
- PRESSURE AND TEMPERATURE RATING IS: 200 PSI @ 250°F

CERTIFIED _____ by _____				COPYRIGHT 2002 AMETEK DREXELBROOK
PO # _____				SCALE NONE UNLESS OTHERWISE STATED ALL DIMENSIONS IN INCHES (MM)
ENG _____	2	8-02-333		DR. JJS 8-16-02
USER _____	1	6-02-331	JEN 7-2-02	CK. _____
	A	5-23-02-TDH-3	TDH 5-23-02	
DE # _____	ISS.	EDO/DSR NO.	APP'D	DATE

AMETEK®
DREXELBROOK

205 KEITH VALLEY RD
HORSHAM, PA 19044-9986

215-674-1234
FAX 215-674-2731

Z-TRON III
CUSTOMER DRAWING,
240 VAC

Z03-205-X-CD

SHT. 1 OF 1
ISS. OF 1 | 2

NO. Z03-205-X-CD